

# APIO '18 P1 - New Home

---

**Time limit:** 2.5s    **Memory limit:** 1G

---

Wu-Fu Street is an incredibly straight street that can be described as a one-dimensional number line, and each building's location on the street can be represented with just one number. Xiao-Ming the Time Traveler knows that there are  $n$  stores of  $k$  store-types that had opened, has opened, or will open on the street. The  $i$ -th store can be described with four integers:  $x_i, t_i, a_i, b_i$ , representing the store's location, the store's type, the year when it starts its business, and the year when it is closed.

Xiao-Ming the Time Traveler wants to choose a certain year and a certain location on Wu-Fu Street to live in. He has narrowed down his preference list to  $q$  location-year pairs. The  $i$ -th pair can be described with two integers:  $l_i, y_i$ , representing the location and the year of the pair. Now he wants to evaluate the life quality of these pairs. He defines the inconvenience index of a location-year pair to be the inaccessibility of the most inaccessible store-type of that pair. The inaccessibility of a location-year pair to store-type  $t$  is defined as the distance from the location to the nearest type- $t$  store that is open in the year. We say the  $i$ -th store is open in the year  $y$  if  $a_i \leq y \leq b_i$ . Note that in some years, Wu-Fu Street may not have all the  $k$  store-types on it. In that case, the inconvenience index is defined as  $-1$ .

Your task is to help Xiao-Ming find out the inconvenience index of each location-year pair.

## Input

---

The first line of input contains integer numbers  $n, k$ , and  $q$ : number of stores, number of types and number of queries ( $1 \leq n, q \leq 3 \times 10^5, 1 \leq k \leq n$ ).

Next  $n$  lines contain descriptions of stores. Each description is four integers:  $x_i, t_i, a_i$ , and  $b_i$  ( $1 \leq x_i, a_i, b_i \leq 10^8, 1 \leq t_i \leq k, a_i \leq b_i$ ).

Next  $q$  lines contain the queries. Each query is two integers:  $l_i$ , and  $y_i$  ( $1 \leq l_i, y_i \leq 10^8$ ).

## Output

---

Output  $q$  integers: for each query output the inconvenience index.

## Scoring

---

### Subtask 1 (points: 5)

$n, q \leq 400$

### Subtask 2 (points: 7)

$n, q \leq 6 \times 10^4, k \leq 400$

### Subtask 3 (points: 10)

$n, q \leq 3 \times 10^5, a_i = 1, b_i = 10^8$  for all stores.

#### Subtask 4 (points: 23)

$n, q \leq 3 \times 10^5$ ,  $a_i = 1$  for all stores.

#### Subtask 5 (points: 35)

$n, q \leq 6 \times 10^4$

#### Subtask 6 (points: 20)

$n, q \leq 3 \times 10^5$

#### Sample Input 1

---

```
4 2 4
3 1 1 10
9 2 2 4
7 2 5 7
4 1 8 10
5 3
5 6
5 9
1 10
```

#### Sample Output 1

---

```
4
2
-1
-1
```

#### Sample Input 2

---

```
2 1 3
1 1 1 4
1 1 2 6
1 3
1 5
1 7
```

## Sample Output 2

---

```
0
0
-1
```

## Sample Input 3

---

```
1 1 1
100000000 1 1 1
1 1
```

## Sample Output 3

---

```
99999999
```

## Explanation

---

In the first example there are four stores, two types, and four queries.

- First query: Xiao-Ming lives in location 5 in year 3. In this year, stores 1 and 2 are open, distance to store 1 is 2, distance to store 2 is 4. Maximum is 4.
- Second query: Xiao-Ming lives in location 5 in year 6. In this year, stores 1 and 3 are open, distance to store 1 is 2, distance to store 3 is 2. Maximum is 2.
- Third query: Xiao-Ming lives in location 5 in year 9. In this year, stores 1 and 4 are open, they both have type 1, so there is no store of type 2, inconvenience index is -1.
- Same situation in fourth query.

In the second example there are two stores, one type, and three queries. Both stores have location 1, and in all queries Xiao-Ming lives at location 1. In first two queries at least one of stores is open, so answer is 0, in third query both stores are closed, so answer is -1.

In the third example there is one store and one query. Distance between locations is 99999999.