

# CCC '12 S2 - Aromatic Numbers

**Time limit:** 2.0s    **Memory limit:** 256M

## Canadian Computing Competition: 2012 Stage 1, Senior #2

This question involves calculating the value of *aromatic* numbers which are a combination of Arabic digits and Roman numerals.

An aromatic number is of the form  $ARARAR \dots AR$ , where each  $A$  is an Arabic digit, and each  $R$  is a Roman numeral. Each pair  $AR$  contributes a value described below, and by adding or subtracting these values together we get the value of the entire aromatic number.

An Arabic digit  $A$  can be 0, 1, 2, 3, 4, 5, 6, 7, 8 or 9. A Roman numeral  $R$  is one of the seven letters I, V, X, L, C, D, or M. Each Roman numeral has a base value:

Symbol	I	V	X	L	C	D	M
Base value	1	5	10	50	100	500	1000

The value of a pair  $AR$  is  $A$  times the base value of  $R$ . Normally, you add up the values of the pairs to get the overall value. However, wherever there are consecutive symbols  $ARA'R'$  with  $R'$  having a *strictly bigger* base value than  $R$ , the value of pair  $AR$  must be *subtracted* from the total, instead of being *added*.

For example, the number  $3M1D2C$  has the value  $3 \times 1000 + 1 \times 500 + 2 \times 100 = 3700$  and  $3X2I4X$  has the value  $3 \times 10 - 2 \times 1 + 4 \times 10 = 68$ .

Write a program that computes the values of aromatic numbers.

## Input Specification

The input is a valid aromatic number consisting of between 2 and 20 symbols.

## Output Specification

The output is the decimal value of the given aromatic number.

## Sample Input 1

```
3M1D2C
```

## Output for Sample Input 1

3700

## Sample Input 2

---

2I3I2X9V1X

## Output for Sample Input 2

---

-16